



Performance and Innovation in Aesthetic

NEW PRODUCT TECHNICAL SHEET

4029

CLAY WIPE **DETAILING CLAY CLOTH**

Description :

The latest innovation in paint decontamination technology is the Clay Wipe from Auto-Chem; this detailing clay cloth easily held in hand, safely eliminates pollutants ingrained in contaminated surfaces.

This innovative Clay Wipe is a positive alternative to the traditional clay bar, faster, efficient, economical and will last for more than 30 vehicles. Clay Wipe is made of "elastic polymer media" which mould the hand to decontaminate any surface. It can be used over and over again, even if dropped on the floor, dust falls off when left in a bucket of water for a few hours.

Your vehicle paint is assaulted every minute by air contaminants and pollutants. Even after thorough washing, you will notice the number of contaminants still present on the paint of your car by putting your hand in a plastic bag and gently pressing your fingers on the surface of the paint. If you experience a grainy texture, it must be decontaminated. These pollutants are brake and train rail dust, paint overspray, tar, tree sap and industrial fall out.

Technical note: the Clay Wipe will not restore scratches and oxidized paint. A shiny finish will be achieved only by polishing the paint after decontamination. Polishing only is not enough to eliminate any contamination on paint, which will affect the adhesion and durability of a sealant or wax.

Advantages :

- Faster than regular clay bar.
- Removes contamination from brake dust, overspray, tar and tree sap
- Great for all surfaces such as, paint, windows and chrome.
- Safe for body shops.
- Will last for more than 30 cars.

Instructions :

1. Always work on a cool surface, not in direct sunlight
2. Wash vehicle very well to loosen surface dirt. Clay Wipe should always be used on freshly washed clean surfaces. Otherwise, dirt on the surface could cause scratches.
3. Work on areas of about 1 square meter, begin at the top and work your way down towards the bottom of the car. Lightly mist the surface with SHOW ROOM Wax Clean & Shine n° 604-032 or use ULTRA BRITE Concentrated Car Wash n° 801-032 mixed with water. Glide the detailing clay cloth across the lubricated area with out putting any excessive pressure until finish is smooth and contaminants are removed.
4. Wipe the surface with a clean microfiber towel.
5. Continue in sections until the entire vehicle is completed.

After claying the surface, you have two options. If the vehicle's paint is in like-new condition (good paint gloss and no swirls), you can finish by applying POLY GLAZE Polymers Liquide Wax n° 600-016 or CRYSTAL SEAL Correcting Sealant n° 680-016. If the finish shows any swirls or scratches, polish with HSF 2 finishing Cut Advanced Compound n° 672-032 or a HSF 3 Advanced finishing Glaze n° 673-032 and then apply a final coat of wax or paint sealant.

n° 4029 Clay Wipe size 30X30cm packaging plastic clam shell

