



SAFETY DATA SHEET

1 – IDENTIFICATION

IDENTIFIER	BOOTH COATING
PRODUCT CODE	947-01, 947-05
RECOMMENDED USE	Peelable paint booth coating – clear.
RESTRICTIONS ON USE	Industrial use only
SUPPLIER / MANUFACTURER	AUTO-CHEM INC 33 de Lyon Repentigny, QC J5Z 4Z3 450-654-9292 www.autochem.com
EMERGENCY TELEPHONE	CANUTEC 1-613-996-6666 (24 hours)

2 – HAZARD IDENTIFICATION

CLASSIFICATION	Not classified under WHMIS 2015.	
LABEL ELEMENTS	None.	
SIGNAL WORD	None.	
HAZARD STATEMENT	None.	
PRECAUTIONARY STATEMENTS – PREVENTION	None.	
PRECAUTIONARY STATEMENTS – RESPONSE	None.	
PRECAUTIONARY STATEMENTS – STORAGE	None.	
PRECAUTIONARY STATEMENTS - ELIMINATION	P501	Dispose contents/containers according to municipal, provincial and federal regulations.
OTHER HAZARDS	Not applicable.	

3 – COMPOSITION / INFORMATION ON INGREDIENTS

CHEMICAL NAME	C.A.S	CONCENTRATION
2-Butoxyethanol	111-76-2	0.5 – 1.5 *
Tris (2-butoxyethyl) phosphate	78-51-3	0.5 – 1.5 *

* TRADE SECRET STATEMENT: The exact concentration of composition has been withheld as a trade secret.

4 – FIRST AID MEASURES

ROUTE OF EXPOSURE	Inhalation, eyes, skin, ingestion
-------------------	-----------------------------------

INHALATION	IF INHALED: remove person to fresh air and keep comfortable for breathing. If experiencing respiratory symptoms: Call a POISON CONTROL CENTER or physician.
DERMAL	IF ON SKIN: Take off immediately all contaminated clothing. Rinse skin with water. If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse.
OCULAR	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
ORAL	NEVER give anything orally if victim is losing consciousness, is unconscious or having convulsions. Rinse mouth with water thoroughly. DO NOT INDUCE VOMITING. Ask victim to drink two glasses of water. If vomiting occurs naturally, lean victim forward to reduce risks of aspiration. Continue to drink water. Obtain medical care.
NOTE TO PHYSICIAN	Specific treatment: Treat symptomatically.

5 – FIRE-FIGHTING MEASURES

SUITABLE EXTINGUISHING MEDIA	According to the conditions of the fire.
UNSUITABLE EXTINGUISHING MEDIA	Direct water jet may disperse the product.
SPECIFIC HAZARDS	Acrid smoke, carbon oxides.
PROTECTIVE EQUIPMENT	Fire-fighters must wear protective equipment and NIOSH approved self-contained breathing apparatus.
PRECAUTIONS	Do not let water run-off reach sewers, ditches or waterways.

6 – ACCIDENTAL RELEASE MEASURES

PROTECTIVE EQUIPMENT	Wear appropriate respiratory equipment (See Section 8). Avoid direct contact with product. Remove non-essential personnel.
CONTAINMENT AND CLEAN UP	Ventilate spill area. Stop spill if safe to do so. Contain and absorb with an inert absorbing material for future disposal (See Section 13). Prevent spill from entering sewers or waterways. Retain water run-off if applicable. Inform proper authorities if necessary.
ENVIRONMENTAL PRECAUTIONS	Avoid entering sewers, waterways or restricted areas. Eliminate according to municipal, provincial and federal regulations.

7 – HANDLING AND STORAGE

HANDLING	Containers must be identified correctly. Handle in a well ventilated area. Avoid breathing dust, vapours or mists. Avoid contact with eyes, skin and clothes. Keep containers closed when not in use. Empty containers may contain residues and must be handled as hazardous waste. Maintain good personal hygiene before eating, drinking or smoking. Do not eat, drink or smoke while using the product or in proximity. Wash contaminated clothing before reuse.
STORAGE	Store in a well-ventilated place. Keep cool. Store away from incompatible materials. Keep containers closed.
INCOMPATIBLE MATERIALS	Strong acids, mineral salts.

8 – EXPOSURE CONTROLS / PERSONAL PROTECTION

CHEMICAL NAME	C.A.S.	SOURCE	VALUE
2-Butoxyethanol	111-76-2	ACGIH OSHA NIOSH NIOSH CSST CSST	TLV 0.2 mg/m ³ TWA 1 mg/m ³ TWA 1 mg/m ³ IDLH 15 mg/m ³ TWA 1 mg/m ³ STEL 3 mg/m ³
Tris (2-butoxyethyl) phosphate	78-51-3		No established limits.

ENGINEERING CONTROLS	Use process enclosures, local exhaust ventilation or other engineering controls to maintain airborne levels to an acceptable level.
RESPIRATORY PROTECTION	Maintain atmospheric concentrations below exposure limits. If exposure exceeds occupational exposure limits, use an appropriate NIOSH approved respirator. In case of spill or leak resulting in unknown concentration, use a NIOSH approved supplied air respirator.
PROTECTIVE EQUIPMENT AND CLOTHING	Wear chemical / impermeable gloves or other protective clothing to prevent repeated or continuous contact with the skin during handling and usage. Wear goggles to prevent mist, vapours or dust to contact eyes. Insure that eyewash stations, showers and cleaning stations are near to work station.
OCULAR PROTECTION	Chemical goggles; also wear a face shield if splashing hazard exists.
GENERAL HYGIENE RECOMMENDATIONS	Ensure that eyewash stations and safety showers are proximal to the work-station location. Avoid production of high concentrations of dust, vapours or mists. Avoid contact with skin and eyes. Avoid breathing dust, vapours or mists. Never eat, drink or smoke near work stations. Good hygiene is recommended after using this product. Clean clothing before reuse.

9 – PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE	Milky white liquid.
ODOUR	Slight.
ODOUR TRESHOLD	Not available.
pH	7.50
MELTING / FREEZING POINT	Not available.
INITIAL BOILING POINT	Not available.
FLASH POINT	Not applicable.
EVAPORATION RATE	Not available.
FLAMMABILITY	Not flammable.
LOWER FLAMMABLE/EXPLOVISE LIMIT	Not applicable.
UPPER FLAMMABLE/EXPLOSIVE LIMIT	Not applicable.
VAPOUR PRESSURE	Not available.
VAPOUR DENSITY	Not available.
RELATIVE DENSITY	1.05
SOLUBILITY (in water)	Soluble.
PARTITION COEFFICIENT (n-octanol/water)	Not available.

AUTO-IGNITION TEMPERATURE	Not available.
DECOMPOSITION TEMPERATURE	Not available.
VOC	21 g/L (0.020 Kg/Kg)
VISCOSITY	1600 cPs

10 – STABILITY AND REACTIVITY

REACTIVITY	Stable under recommended usage.
CHEMICAL STABILITY	Stable under normal usage conditions.
HAZARDOUS REACTIONS	Polymerization will not occur.
CONDITIONS TO AVOID	Incompatible materials.
INCOMPATIBLE MATERIALS	Strong acids, mineral salts.
HAZARDOUS DECOMPOSITION PRODUCTS	Carbon oxides.
ADDITIONAL INFORMATION	None.

11 – TOXICOLOGICAL INFORMATION

ACUTE EFFECTS	
INHALATION	No adverse effects reported.
DERMAL	May irritate sensitive subjects.
OCULAR	May irritate by mechanical action in direct contact.
ORAL	May cause gastric distress, nausea, vomiting.
CHRONIC EFFECTS	
INHALATION	No data.
DERMAL	No data.
OCULAR	No data.
ORAL	No data.
ADDITIONAL INFORMATION	
CARCINOGENIC EFFECTS (IARC)	2-Butoxyethanol 111-76-2 Group 3: Not classifiable as to its carcinogenicity to humans.
MUTAGENIC EFFECTS	No data.
TERATOGEN EFFECTS	No data.
REPRODUCTION	No data.
SENSIBILISATION	No data.
TARGET ORGANS	No data.
AGGRAVATED CONDITIONS	No data.
SYNERGISTIC SUBSTANCES	No data.

CHEMICAL NAME	C.A.S.	LD50 ORAL mg/kg	LD50 DERMAL mg/kg	LC50 INHALATION
2-Butoxyethanol	111-76-2	560, rat	400, rabbit	450 ppm. 4 h, rat

Tris (2-butoxyethyl) phosphate	78-51-3	3000, rat	> 5000, rat	30 mg/L, 4h, rat
--------------------------------	---------	-----------	-------------	------------------

12 – ECOLOGICAL INFORMATION

2-Butoxyethanol	111-76-2
LC50 1490 mg/L, 96h, static	Lepomis macrochirus
LC50 2950 mg/L, 96h	Lepomis macrochirus
LC50 1474 mg/L, 96 h, static	Oncorhynchus mykiss
EC50 1800 mg/L, 48 h, static	Daphnia magna
EC50 977 mg/L, 72 h, static	Pseudokirchneriella subcapitata

Tris (2-butoxyethyl) phosphate	78-51-3
LC50 24 mg/L 96h	Oncorhynchus mykiss
EC50 53 mg/L, 48h	Daphnia magna
EC50 61 mg/L, 72h	Pseudokirchneriella subcapitata

PERSISTENCE AND DEGRADABILITY	Not available.
BIOACCUMULATIVE POTENTIAL	Not available.
SOIL MOBILITY	Not available.
OTHER ADVERSE EFFECTS	Not available.
ADDITIONAL INFORMATION	Do not let material or fire-fighting water run-off enter sewers or waterways. Obstruct drains and ditches. Affected areas must be cleaned and restored to their original conditions or to the satisfaction of the authorities.

13 – DISPOSAL CONSIDERATIONS

DISPOSAL METHOD	Disposal of all wastes must be done in accordance with municipal, provincial and federal regulations.
CONTAMINATED PACKAGING	Empty containers should be recycled or disposed of through an approved waste management facility.

14 – TRANSPORT INFORMATION

TRANSPORT OF DANGEROUS GOODS (CANADA)
Not regulated for transport.

MARINE POLLUTANT	No.
SPECIAL PRECAUTIONS	Avoid freezing.

15 – REGULATORY INFORMATION

CANADA	
--------	--

CEPA	All components of this product are either listed or exempt from listing on the Domestic substances List (DSL).
USA	
TSCA	All components of this product are either listed or exempt from listing on the Toxic Substances Control Act (TSCA) Inventory.

16 – OTHER INFORMATION

VERSION	1.0
DATE	21 November 2017
PREPARED BY	AUTO-CHEM INC
ABBREVIATIONS	ABBREVIATIONS
ACGIH	American Conference of Governmental Industrial Hygienists
AIHA	American Industrial Hygiene Association
CAS	Chemical Abstract Service
CEPA	Canadian Environmental Protection Act
CIRC	Centre International pour la Recherche sur le Cancer
CL / LC	Concentration létale /Lethal concentration
DL / LD	Dose létale / Lethal dose
CE / EC	Concentration efficace / Effective concentration
IARC	International Agency for Research on Cancer
LCPE	Loi Canadienne sur la Protection de l'Environnement
LES/NDSL	Liste extérieure des substances / Non domestic substances list
LIS/DSL	Liste intérieure des substances / Domestic substances list
NIOSH	National Institute for Occupational Safety and Health
NTP	National Toxicology Program (U.S.A.)
OSHA	Occupational Safety and Health Administration (U.S.A.)
PEL	Permissible Exposure Limit
SIMDUT	Système d'information sur les matières dangereuses utilisées au travail
STEL	Short-term Exposure Limit
STOT	Specific target organ toxicity
TCOC	Toxicité pour certains organes cibles
TLV	Threshold Limit Value
TSCA	Toxic Substances Control Act
TWA	Time Weighted Average
USEPA	United States Environmental Protection Agency
VECD	Valeur exposition courte durée
VEMP	Valeur exposition moyenne pondérée
WHMIS	Workplace Hazardous Materials Information System
NOTICE TO READER	All information appearing herein is based upon data obtained from the manufacturer and/or recognized technical sources. While the information is believed to be accurate, Auto-Chem makes no representations as to its accuracy or sufficiency. Conditions of use are beyond Auto-Chem's control and therefore users are responsible to verify this data under their own operation conditions to determine whether the product is suitable for their particular purposes and they assume all risks of their use, handling and disposal of the product or from the publication or use of, or reliance upon, information contained herein. This information relates only to the product designated herein, and does not relate to its use in combination with any other material or in any other process